DOBER REVIVE

PRODUCT FACTS

Alkaline-Based Radiator Cleaner & Flush

FEATURES

- · Effective, safe, and easy to use
- · Dissolves scale and corrosion products
- · Removes oil and grease residues
- · One Step

- · Does not effect hoses and seals
- · Non-foaming

TYPICAL PROPERTIES

- Color : Clear
- Approximate pH: 12.2
- · Approximate Density: 9.0 lbs / gallon

GENERAL PROPERTIES

Physical properties of Dober Revive are shown on the Material Safety Data Sheet, a copy of which is available upon request.

DESCRIPTION AND USE

Dober Revive is a versatile engine flush for removing deposits found in heavy and light duty cooling systems. Dober Revive is easily applied during routine maintenance schedules. Regular use preserves engine efficiency and extends the life of cooling system components by removing scale or sludge and by maintaining system cleanliness.

Clean cooling systems prevent increases in cooling water temperatures and eliminate failures that result from loss of heat transfer at radiators, cylinder liners, piston heads, and other components that physically contact the coolant.

TREATMENT AND FEEDING REQUIREMENTS

Drain coolant, flush and fill system with water. Add 6-8% by volume and recirculate at 180°F for one hour. Drain cleaning solution & flush with water until clear.



PACKAGING INFORMATION

Dober Revive is blended as a liquid and is supplied in a variety of packages including drums and pails. Ask your representative for more information.



STORAGE AND HANDLING

Store Dober Revive at moderate temperatures of 30° to 100°F (-1° to 38°C). To ensure maximum activity this product should be used within two years from the date of manufacture. Keep containers closed when not in use.



SAFETY PRECAUTIONS

Product may cause moderate irritation to the skin and is a severe irritant to the eyes. Mists / aerosols may cause irritation to upper respiratory tract. If material comes in contact with skin or eyes, wash skin thoroughly and flush eyes with water. Seek immediate medical attention.

For additional information contact Dober at: 630-410-7300 coolantinfo@dober.com www.dober.com

